

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 October 2001 (25.10.2001)

PCT

(10) International Publication Number
WO 01/78881 A1

(51) International Patent Classification⁷: **B01D 61/02**,
61/58, C12G 3/08, C12H 1/04, B01D 15/00

DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(21) International Application Number: PCT/IB01/00383

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(22) International Filing Date: 15 March 2001 (15.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2000/1900 14 April 2000 (14.04.2000) ZA

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicant and


(72) Inventor: TUDHOPE, Bryan, Richard [ZA/ZA]; Unit 3
Loneridge, 207 Swatrgoud Street, 2091 Ridgeway (ZA).

(74) Agent: JOHN & KERNICK; P.O. Box 3511, Halfway
House 1685 (ZA).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR ISOLATING AND/OR ELIMINATING SOLUTES FROM A SOLUTION



WO 01/78881 A1

(57) Abstract: This invention relates to an apparatus for removing solutes from a solution using a nano-filtration means to provide a treated solution.

5

10

**APPARATUS AND METHOD FOR ISOLATING AND/OR ELIMINATING
SOLUTES FROM A SOLUTION**

15 **FIELD OF THE INVENTION**

This invention relates to the isolation and/or elimination of solutes from a solution, more particularly from beverages.

BACKGROUND TO THE INVENTION

20 It is well-known in the art that during the course of the production of certain beverages, compounds are produced which detract from the flavour and quality of the beverage. This is a particular problem associated with the production of alcoholic beverages where compounds such as ethyl acetate, acetic acid, and acetaldehyde are detrimental to the flavour and aroma of the alcoholic beverage.

25

It is also known in the art that such undesirable compounds may be removed from solution by means of reverse osmosis. This process of reverse osmosis requires elevated pressures to achieve its effect, resulting in an increase in temperature. It is commonly known that certain volatile components in solution are adversely affected by an increase in 30 temperature that leads to associated unfavourable development of derivatives of integral solutes in solution, or even more unfavourably the generation of contaminating

CONFIRMATION COPY

compounds in solution. Reverse osmosis also only removes up to 15% of the volatile acidity from the wine in a single pass. If higher levels are to be removed using the reverse osmosis process, the wine has to then be passed 2-3 times which can lead to a further deterioration in the whole quality of the wine as well as excessive increases in
5 temperature. To limit, insofar as possible, the effects of the reverse osmosis on the quality of the treated solution heat exchangers are utilised, which is costly and cumbersome.

Ultra-filtration is also known to remove unwanted compounds from a solution. However, this requires low pressure with concomitant detrimental effects to the solution insofar as
10 desirable compounds also pass through into the permeate.

OBJECT OF THE INVENTION

It is an object of the invention to provide an apparatus, which, at least partially, alleviates the above-mentioned problems.
15

It is a further object of the invention to provide a method, which, at least partially, alleviates some of the above-mentioned problems.

SUMMARY OF THE INVENTION

20 In accordance with the invention there is provided an apparatus for removing at least one solute from a solution comprising a receptacle for a solution; a nano-filtration means in fluid communication with the receptacle; a means for driving the solution through the nano-filtration means to produce a retentate at a retentate outlet and a raw permeate at a raw permeate outlet; a separation means having an inlet which is in fluid communication
25 with the raw permeate outlet of the nano-filtration means and a treated permeate effluent outlet which is in fluid communication with the retentate outlet which, in use, combines the retentate egressing from the retentate outlet with the treated permeate egressing from the treated permeate effluent outlet to provide a treated solution.

In accordance with this embodiment of the invention the separation means is preferably a treatment column, the column being an ion exchange column, alternatively a hydrophobic interaction column, further alternatively an affinity column, still further alternatively a gel filtration or gel exclusion column.

5 In accordance with a further embodiment of the invention there is an apparatus for removing at least one solute from an untreated alcoholic beverage comprising a receptacle for the untreated alcoholic beverage; a nano-filtration means in fluid communication with the receptacle; a means for driving the untreated alcoholic beverage
10 through the nano-filtration unit to produce a retentate at a retentate outlet and a raw permeate at a raw permeate outlet; an anion exchange column having an inlet which is in fluid communication with the raw permeate outlet of the nano-filtration unit and a treated permeate effluent outlet which is in fluid communication with the retentate outlet which, in use, combines the retentate egressing from the retentate outlet with the treated permeate
15 egressing from the treated permeate effluent outlet to provide a treated untreated alcoholic beverage.

Furthermore, in accordance with the invention there is provided a method for treatment of a solution to remove at least one solute from a solution, including the steps of subjecting
20 the solution to a process of nano-filtration for producing a retentate and a raw permeate, with the raw permeate containing the solute; treating the raw permeate for removing at least a portion of the solute to provide a treated permeate; and combining the retentate and the treated permeate to provide a treated solution, preferably the treatment of the raw permeate occurs under high pH conditions on an anion exchange column.

25
BRIEF DESCRIPTION OF THE DRAWINGS
One embodiment of the invention is described below, by way of example only, with reference to the accompanying drawing where:

Figure 1 is a schematic view of apparatus for isolating and/or eliminating a solute from a solution.

5 **DETAILED DESCRIPTION WITH REFERENCE TO THE DRAWINGS**

With reference to the drawing an apparatus (1) for removing a compound (not shown) of interest from an untreated alcoholic beverage (12) is illustrated. The apparatus (1) has a receptacle (10) which receives the untreated alcoholic beverage (12), a nano-filtration unit (14) which is in fluid communication with the receptacle (10) and a pump (16) to drive the untreated alcoholic beverage (12) through the nano-filtration unit (14) to produce a retentate (not shown) at a retentate outlet (18) and a raw permeate (not shown) at a raw permeate outlet (20) and a anion exchange column (22) having an inlet (24) which is in fluid communication with the raw permeate outlet (20) of the nano-filtration unit (14) and a treated permeate effluent outlet (26) which is in fluid communication with the retentate outlet (18) which, when the apparatus (1) is in use, combines the retentate (not shown) egressing from the retentate outlet (18) with the treated permeate (not shown) egressing from the treated permeate effluent outlet (26) to provide a treated alcoholic beverage (not shown).

10 One embodiment of the method for treatment of an untreated alcoholic beverage (12) to remove at least one compound (not shown) from the untreated alcoholic beverage (12) includes the steps of subjecting the untreated alcoholic beverage (12) to a process of nano-filtration through the nano-filtration unit (14) to produce a retentate (not shown) and a raw permeate (not shown), with the raw permeate (not shown) containing the compound

15 to be removed from the raw permeate (not shown) followed by treating the raw permeate (not shown) by passage through an anion exchange column under high pH conditions (22) thereby removing at least a portion of the compound (not shown) to provide a treated permeate (not shown); and combining the retentate (not shown) and the treated permeate (not shown) to provide a treated alcoholic beverage.

20

25

It will be appreciated that numerous variations, which will be apparent to those skilled in the art, can be made to the above-mentioned embodiment of the invention without departing from the scope thereof. In particular the means for driving the untreated
5 solution through the nano-filtration unit may be gravity-based.

Claims

1. An apparatus for removing at least one solute from a solution comprising a receptacle for a solution; a nano-filtration means in fluid communication with the receptacle; a means for driving the solution through the nano-filtration means to produce a retentate at a retentate outlet and a raw permeate at a raw permeate outlet; a separation means having an inlet which is in fluid communication with the raw permeate outlet of the nano-filtration means and a treated permeate effluent outlet which is in fluid communication with the retentate outlet which, in use, combines the retentate egressing from the retentate outlet with the treated permeate egressing from the treated permeate effluent outlet to provide a treated solution.
2. An apparatus as claimed in claim 1, wherein the separation means is a treatment column.
3. An apparatus as claimed in claim 2 wherein the column is an ion exchange column.
4. An apparatus as claimed in claim 2 wherein the column is a hydrophobic interaction column.
5. An apparatus as claimed in claim 2 wherein the column is an affinity column.
6. An apparatus as claimed in claim 2 wherein the column is a gel filtration- column or gel exclusion column.
7. An apparatus as claimed in claim 1 for removing at least one solute from an untreated alcoholic beverage comprising a receptacle for the untreated alcoholic beverage; a nano-filtration means in fluid communication with the receptacle; a means for driving the untreated alcoholic beverage through the nano-filtration unit to produce a retentate at a retentate outlet and a raw permeate at a raw permeate

outlet; an anion exchange column having an inlet which is in fluid communication with the raw permeate outlet of the nano-filtration unit and a treated permeate effluent outlet which is in fluid communication with the retentate outlet which, in use, combines the retentate egressing from the retentate outlet with the treated permeate egressing from the treated permeate effluent outlet to provide a treated untreated alcoholic beverage.

8. A method for treatment of a solution to remove at least one solute from a solution, including the steps of subjecting the solution to a process of nano-filtration for producing a retentate and a raw permeate, with the raw permeate containing the solute; treating the raw permeate for removing at least a portion of the solute to provide a treated permeate; and combining the retentate and the treated permeate to provide a treated solution, preferably the treatment of the raw permeate occurs under high pH conditions on an anion exchange column.
9. An apparatus as claimed in any one of claims 1 to 7, including any new and inventive integer or combination thereof herein described.
10. An apparatus as claimed in any one of claims 1 to 7, including any new and inventive integer or combination thereof herein exemplified.
11. A method as claimed in claim 8, including any new and inventive integer herein described.

1/1




Figure 1

INTERNATIONAL SEARCH REPORT

Int'l	ional Application No
PCT/IB 01/00383	

A. CLASSIFICATION OF SUBJECT MATTER	IPC 7	B01D61/02	B01D61/58	C12G3/08	C12H1/04	B01D15/00
-------------------------------------	-------	-----------	-----------	----------	----------	-----------

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01D C12G C12H A23L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 93 23151 A (C.SMITH) 25 November 1993 (1993-11-25) abstract; claims -----	1-3, 7-11

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

7 August 2001

Date of mailing of the international search report

16/08/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Palentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cordero Alvarez, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/IB 01/00383

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
WO 9323151	A	25-11-1993	AT 171390 T	15-10-1998
			AU 661912 B	10-08-1995
			AU 4231993 A	13-12-1993
			BG 62318 B	31-08-1999
			BG 99165 A	28-08-1995
			CA 2135305 A	25-11-1993
			DE 69321229 D	29-10-1998
			DE 69321229 T	18-02-1999
			DK 639105 T	14-06-1999
			EP 0639105 A	22-02-1995
			ES 2123053 T	01-01-1999
			HU 70805 A,B	28-11-1995
			US 5480665 A	02-01-1996
			ZA 9303213 A	14-06-1994